

65F0911

Flyaway Axle Jack



333065

65 TON

Updated 04/01/24

STANDARD FEATURES

- ID chrome-plated plungers
- Hydraulic fuse prevents lowering load, in the event of a fluid line failure
- Two manual hand pumps (high pressure, low volume & low pressure, high volume)
- Single valve control for raise and lower of aircraft
- Control console with instruction decals
- Rain hat
- Oil filter cap with filtered air vent and dipstick
- Swivel casters with retractable front caster
- all non-painted parts are plated for corrosion resistance
- 1 year standard warranty

OPTIONAL FEATURES (Add suffix to model #)

- E: Extended Adapter for B747-8

PACKAGING OPTIONS

SKID: domestic skid (included)

CRATE: Jack shipped in international crate

SHIPPING DIMENSIONS:



Length	Width	Height	Weight
51 in.	19 in.	25 in.	280 lbs.

SPECIFICATIONS	STANDARD	METRIC
Rated Capacity	65 tons	59 m tons
Low Height	9.25 in	235 mm
Hydraulic Lift	11 in	279 mm
Extension Screw	4.75 in	121 mm
Total Extended Height	25 in	635 mm
Base Width	8.75 in	222 mm
Cylinder Diameter	8 in	203 mm
Oil Pressure at Rated Capacity	7000 psig	492 kg/sq cm
Safety Pop-off Valve Set at	68.9 tons	62.5 m tons
Proof Load	97.5 tons	88.5 m tons
Floor Loading at Rated Capacity	825 psi	58 kg/sq cm
Reservoir Capacity	5.5 gal	20.8 ltr
Hydraulic Fluid	MIL-PRF-5606 or eq.	MIL-PRF-5606 or eq.
Maximum Towing Speed	5 mph	8 km/h
Approximate Jack Net Weight	205 lbs	93.0 kg

TYPICAL AIRCRAFT APPLICATIONS

MAIN LANDING GEAR

A300, A310, A319, A320, A321, A330, A340-200/-300 B707, B717, B720, B727, B737, B747, B757, B767, B787 DC8, DC10, L1011, MD11

NOSE LANDING GEAR

A300, A310, A330, A340-200/-300, A340-500/-600, A350 B727, B747, B747-8 B757, B767, B777, B787 DC10, L1011, MD11

PURCHASE ORDERS

ATAP, Inc.
130 Industrial Way
Eastaboga, AL 36260
Phone: 256.362.2221
Email: info@atap.com

SPARE PARTS/REPAIR

Manifold & Phalor, Inc.
10385 Busey Road
Canal Winchester, Ohio 43110
Phone: 614.920.1200
Email: sales@manifoldphalor.com



Manifold & Phalor

www.mpi-gse.com